



219.00 EUR  
incl. 19% VAT, plus [shipping](#)



Support: [Specifications \[EN\]](#)

- Intel® Q67 Express Chipset
  - Supports Intel LGA 1155 Socket Core™ i3, i5, i7 & Pentium Processors
  - 2 \* Dual Channel DDR3-1333/1066 up to 16GB
  - Intel 82579LM & 82574L Gigabit LAN
  - Intel Active Management Technology ( iAMT 7.0)
  - PCI Express x16 Slot
  - Integrated 24-bit Dual Channel LVDS
  - 4-port SATAII 3Gb/s & 2-port SATA III 6Gb/s with RAID 0, 1, 5, 10 & JBOD Support
  - HDMI, and VGA Video Outputs
  - Built-in Watchdog Timer Technology
  - Mini-ITX Form Factor (170mm x 170mm)
  - **CPU**
  - **Chipset**
  - **Memory**
  - **Expansion Slots**
  - **Storage**
- |   |
|---|
| INTEL® LGA 1155 Socket Core i7/i5/i3/Pentium Processor                            |
| INTEL® Q67 Chipset  |
| Clock 100MHz  |
| 2 * 240 pin 4GB 1333/1066 Dual CH DDR3 SDRAM DIMM Max. up to 16GB                 |
| 1 *PCIe x 16  |
| 2 * Serial ATA3 6Gb/s & 4 * Serial ATA2 3Gb/s connectors support RAID 0, 1, 5, 10 |

- **Audio** VIA VT1705 6-Channel HD Audio CODEC
- **Ethernet LAN** Intel 82579LM & 82574L PCI-E Gigabit Ethernet LAN
- **LVDS** Onboard 24-bit dual channel LVDS connector
- **USB** Embedded 10 \* USB 2.0/1.1
- **Special Features** Support ACPI S3  
Support CPU Smart FAN  
Support Watch Dog
  
- **Rear Panel I / O** 6 \* USB 2.0/1.1 ports  
1 \* PS2/KB Connector  
2 \* RJ-45 port  
1 \* HDMI port  
1 \* COM port  
1 \* VGA port  
3 \* Audio Phone Jack
  
- **Internal I / O** 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports  
CPU /NB / Chassis Fan connectors  
1 \* GPIO header  
1 \* COM header(RS232/422/485)  
1 \* IR header  
1 \* Chassis Intrusion header  
1 \* AUDIO header  
1 \* 24-pin & 4-pin 12V ATX Power connector
  
- **BIOS** AMI EFI 64MB SMT Flash ROM
- **Form Factor** Mini-ITX Form Factor (170mm x 170mm)
- **Functional** ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
  
- **Certificate** CE, FCC, RoHS
- **Temperature** Operating within 0~60 centigrade  
Storage within -20-85 centigrade

**Product Accessories**

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield