



Support: Specifications | Pictures

D150 is a 15 inch all-in-one computing system with Intel Bay Trail processor in fanless system design. With single touch functionality and protected by IP64 front sealed chassis, all of these are aiming to provide the most stable and reliable quality for wide application and different environmental conditions.

Perfect for Smart Home, Retail POS Terminal, Self service Terminal, Hospitality Terminal, Digital Signage Player, Clinical Monitor, Transportation Display, Automation Controller, Embedded Device Dashboard or Production Line Controller.

Note : CPU not included in scope of supply !

Item	Spec
	Size/Resolution
LCD Display	Luminance
	Viewing Angle
Touch Screen	Туре

15" TFT LCD, 1024 x 768, 4:3 250 cd/m2 70° (L/R), 65° (U/L) 5 wires resistive touch, Flat Glass

9999.00 EUR incl. 19% VAT, plus shipping

- 1024x768 Touchscreen !
- Fanless ! IP64 Front !
- Intel Haswell CPU !
- 2x LAN, 4x COM !



Mitac D150-LR 15" Panel PC (1024x768, Touchscreen, PH12LI Thin-ITX Q87 Haswell, IP64 Front, Fanless) [http://www.cartft.com/catalog/il/2033]

	Form Factor	Thin Mini-iTX, 170 x 170mm
	CPU	Intel Haswell H3 LGA1150 CPU Socket Support up to Dual/Quad core 65W
	Memory	2 x DDR3L-1333 SO-DIMM, up to 16GB
	Storage	1 x 2.5" drive bay
	Ŭ	x 1 PCI Express x 4 slot
Processor System		
	Expansion	x 1 PCI Express Full-/Half-Mini Card slot
		x 1 PCI Express Half-Mini Card slot
		2 x RJ-45; 2 x USB 3.0, 1x Line-Out, 1x Mic-In,1x
	I/O	HD-out
		1x DP-out, 2x RS-232
	Input	12V DC-in connectivity
Power	Power consumption	84W adaptor
	Power On	AT (on when power is ready)
	Size (W x D x H)	280 mm x 355 mm x 55.1 mm
Mechanical	Weight	~5 kg
Mechanical	Protection	IP64 Compliant in front
	Fixture	VESA 75x75/100x100mm, panel Mount
	Operating Temp	-20 ~ 50°C
Environmental	Operating Humidity	10% ~ 90% (relative, non-condensing)
	Certification	CE/FCC Class A