



- Vibration/shock tested

For FleetPC-7-B we offer an [direct connector cable for our TFT-displays](#).

Dimensions / Weight	229mm W x 161mm D x 65mm H, 1.4kg
CPU	Intel Dual Core i3-4010U 1.70 GHz
RAM	1x SO-DDR-3L RAM (up to 8GB)
Graphics	Intel HD Graphics
Expansion	- 4x Mini-PCle
OS Support	Windows 7, Windows 8.1, Windows 10, Linux
Vibration & Shock	MIL-STD-810F
Operating temperature	-40~70°C (with SSD)
Certification	CE, FCC, eMark
	- 2x Gigabit LAN (Intel i210-AT) [PoE 802.3af]
	- 1x Gigabit LAN (Intel i218LM) [vPro]
	- 4x RS232 (2x with 232/422/485)
	- 2x USB3.0
I/O	- 1x USB2.0
	- GPIO port (4in, 4out, with Relay 12V/100mA)
	- Mic-In, SPK Out
	- 1x DVI-I (for DVI-D and VGA), 1x HDMI
	- 4x SMA Antenna hole (for eg. GPS, GSM/GPRS/3G, WLAN, Bluetooth)
Drive bays	1 x 2.5" SATA HDD/SSD drive bay, 1x SATA DOM
	9~36V DC PSU included
Power supply	- Power off Delay Time Setting by Software, Default 5min
	- <a href="#">Backup Battery Kit (optional)</a>
Scope of Supply	- FleetPC-7-B PC mit Intel Core i3-4010U (2x1.7Ghz), Halterung