



999.00 EUR incl. 19% VAT, plus shipping

6-Port Gigabit Switch with 4-Port PoE provides the seamless network connection. It integrates 1000Mbps Gigabit Ethernet and 10/100Mbps Fast Ethernet network capabilities.

6 Auto-Negotiation RJ45 ports (port-1 to port-4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Easy To Use

Easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the 6-Port Gigabit Desktop Switch with 4-Port PoE is a great selection for expanding your home or office network.

Key Features:

Network Media

- * Supports PoE power up to 15.4W for each PoE port
- * Supports PoE power up to 60W for all PoE ports
- * Supports PoE IEEE 802.3af compliant PDs
- * Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- * 4 ports with poe, 1 port 10/100/1000M RJ45 and 1Port Gigabit SFP
- * External power adapter (60W[48V/1.25A])

5 10/100/1000Mbps RJ45 Ports

Interface 1 10/100/1000Mbps SFP Solt

AUTO Negotiation/AUTO MDI/MDIX

10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)

EIA/TIA-568 100Ω STP (maximum 100m)

100BASE-TX: UTP category 5, 5e cable (maximum 100m)

EIA/TIA-568 100Ω STP (maximum 100m)

1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568

 100Ω STP (maximum 100m)

Fan Quantity Fanless

External Power Supply External Power Adapter(Output: 48VDC /1.25A)



[http://www.cartft.com/catalog/il/2207]



Standard: 802.3 af/at compliant

PoE Ports (RJ45) PoE Ports: Port1- Port 4

Power Supply: 60W

Backbound Bandwidth 10Gbps Mac Address Table 4K

Dimensions (W x D x H) (160*90*28 mm)

Transmission Method Store-And-Forward

Compatible With IEEE 802.3af Compliant PDs

Priority Function

Advanced Functions Mac Address Auto-Learning And Auto-Aging

EEE802.3x Flow Control

802.1p/DSCP QoS

Certification CE, FCC, RoHS
Package Contents Switch, Power Adapter

Operating Temperature: 0°C~40°C

Environment Storage Temperature: -40°C~70°C

Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing