



519.00 EUR

incl. 19% VAT, plus [shipping](#)

- HBJC143F693W-H110



- Intel® LGA1151 Socket Core i3,i5,i7 & Pentium Processors(max.65W)
- Support DDR4-2133Mhz, 2 \* SO-DIMM slot, up to 32GB memory
- 2 \* USB2.0, 4 \* USB3.0, 1 \* HDM , 1 \* DP, 2 \* RJ45, 1 \* MIC, 1 \* Line in, 1 \* Line out
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

|                 |   |
|-----------------|---|
| MB Model        | - JNF693-H110 / Mini ITX  |
| Part No         | - HBJC143F693-H110-B (non-WIFI)<br>- HBJC143F693W-H110-B (WIFI)   |
| BIOS            | - AMI 64MB SMT Flash ROM  |
| CPU/Chipset     | - INTEL® LGA1151 Socket Core i3, i5, i7 & Pentium Processors  |
| Memory          | - 2 * DDR4-2133 up to 32GB  |
| Storage         | - 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay<br>- 1 * M.2_SSD (M key-2242/2260)  |
| Network         | - 2 * Realtek® 8111H Gigabit LAN<br>- 1 * Full-size mini-PCIE slot ( 802.11 b/g/n + BT 4.0 installed in WIFI model / Optional )   |
| Rear Panel I/O  | - 4 * USB 3.0<br>- 1 * HDMI (Max Resolution : 3840x2160@24Hz)<br>- 1 * DP (Max Resolution : 4096x2304@60Hz)<br>- 2 * RJ45<br>- 1 * Mic , 1 * Line in , 1 * Line-out (Realtek ALC662)<br>- 6 * RS232<br>- 1 * AC -in CON |
| Front Panel I/O | - 1 * Power button<br>- 1 * Power LED, 1 * HDD LED<br>- 2 * USB 2.0   |
| Power Source    | - 1U 200W FLEX POWER<br>- AC 90~240V input  |
| Compliance      | - CE, FCC, LVDS, RoHS   |
| Temperature     | - Operating Temperature: 0 ~ 50° C<br>- Storage Temperature: -10 ~ 70° C  |
| Dimensions      | - 330 (W) x 192 (D) x 44 (H) mm   |
| Packing         | - Net Weight: 2.0KG<br>- Gross Weight: 3.0KG<br>- Color Box dimension: 406 (W) * 359 (D) * 148 (H) mm   |
| OS Support      | - Windows 7, Windows 8.1, Windows 10, Linux   |
| Warranty        | - 2 Year limited warranty   |