

999.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel® Skylake/Kabylake U-series Processor (Default Celeron 3965U)
- 2 \* 260-pin Dual-channel DDR4 2133MHz SO-DIMM Up to 32 GB
- 2 \* USB2.0, 6 \* USB3.0, 1 \* COM, 1 \* DP, 1 \* HDMI, 2 \* RJ45, 1 \* Line-in, 1 \* MIC+Line-out Combo
- M/B Form Factor : uTX (117x112mm)
- DC-12V\_40W Adapter

|             |   |                     |
|-------------|---|---------------------|
| MB Model    | – JNU792V-3965 uTX _Celeron 3965U Processor   |                     |
| Part No     | VGA   | VGA & TPM           |
|             | – HBFCU792V-3965-B  | – HBFCU792V-3965-T  |
|             | – HBFCU792VW-3965-B   | – HBFCU792VW-3965-T |
| BIOS        | – AMI 16MB SMT Flash ROM  |                     |
| CPU/Chipset | – Intel® Skylake/Kabylake U-series Processor (Default Celeron 3965U)<br>Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload. |                     |
| Memory      | – 2 * 260-pin Dual-channel DDR4 2133MHz SO-DIMM up to 32 GB   |                     |
| Storage     | – 1 * 2.5" SATAIII 6Gb/s internal drive bay<br>– 1 * full-size mSATA/Mini-PCIe shared slot  |                     |

|                 |   |
|-----------------|---|
| Network         | <ul style="list-style-type: none"> <li>- 1 * Intel i211AT GbE, 1 * Intel i219LM GbE</li> <li>- 1 * half-size Mini-PCIe slot (for WiFi model installed)</li> </ul>   |
| Rear Panel I/O  | <ul style="list-style-type: none"> <li>- 2 * USB 3.0 ports , 2 * USB 2.0</li> <li>- 1 * HDMI 1.4 (Max. 4096 x 2304@24Hz resolution)</li> <li>- 2 * RJ45</li> <li>- 1 * Line-in, 1 * MIC+Line-out Combo (Realtek ALC662VD)</li> <li>- 2 * Antenna holes (WiFi only)</li> <li>- 1 * DC-in jack</li> </ul> |
| Front Panel I/O | <ul style="list-style-type: none"> <li>- 1 * Power button</li> <li>- 1 * Power LED , 1 * HDD LED</li> <li>- 2 * USB 2.0 , 2 * USB 3.0</li> <li>- 1 * VGA</li> </ul>   |
| Power Source    | <ul style="list-style-type: none"> <li>- FSP AC to DC Adapter / DC12V_3.3A_40W</li> <li>- AC 90~240V input</li> </ul>   |
| Compliance      | <ul style="list-style-type: none"> <li>- CE, FCC, LVD, RoHS, ErP Ready</li> </ul>   |
| Temperature     | <ul style="list-style-type: none"> <li>- Operating Temperature: 0 ~ 50° C</li> <li>- Storage Temperature: -10 ~ 70° C</li> </ul>  |
| Dimensions      | <ul style="list-style-type: none"> <li>- 144 (W) x 116.9 (D) x 65 (H) mm</li> </ul>   |
| Packing         | <ul style="list-style-type: none"> <li>- Net Weight: 1.8KG</li> <li>- Gross Weight: 2.8KG</li> <li>- Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm</li> </ul>   |
| OS Support      | <ul style="list-style-type: none"> <li>- 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux</li> </ul>   |
| Warranty        | <ul style="list-style-type: none"> <li>- 2 Year limited warranty</li> </ul>   |