



489.00 EUR  
 incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake SoC Processor
- 1 \* DDR3L SODIMM Up to 8GB
- 4 \* COM, 4 \* USB3.0, 1 \* HDMI, 1 \* DP, 1 \* RJ45, 1 \* MIC, 1 \* Line-in, 1 \* Line-out
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

|                 |   |
|-----------------|---|
| MB Model        | – JNF694L-3350 / Mini ITX<br>– JNF694L-4200 / Mini ITX  |
| Part No.        | – HBJC143F694-335B (non-WIFI) / HBJC143F694W-335B (WIFI)<br>– HBJC143F694-420B (non-WIFI) / HBJC143F694W-420B (WIFI)  |
| BIOS            | – AMI Flash ROM   |
| CPU/Chipset     | – INTEL® Apollo Lake SoC Processor  |
| Memory          | – 1 * DDR3L-1866 MHz up to 8 GB   |
| Storage         | – 1 * 2.5" SATA 6Gb/s_ internal drive bay<br>– 1 * M.2_SSD (M key-2242/2260)  |
| Network         | – 1 * Realtek® 8111H Gigabit LAN<br>– 1 * Full-size mini-PCIE slot ( 802.11 b/g/n + BT 4.0 installed in WIFI model / Optional )   |
| Rear Panel I/O  | – 4 * USB 3.0<br>– 1 * HDMI 1.4 (Max Resolution : 3840x2160@24Hz)<br>– 1 * DP (Max Resolution : 4096x2160@60Hz)<br>– 1 * RJ45<br>– 1 * MIC, 1 * Line-in , 1 * Line-out (Realtek ALC662)<br>– 4 * RS232<br>– 1 * AC-in CON |
| Front Panel I/O | – 1 * Power button, 1 * Reset button<br>– 1 * Power LED, 1 * HDD LED<br>– 2 * USB 2.0   |
| Power Source    | – 1U 200W FLEX POWER<br>– AC 90~240V input  |
| Compliance      | – CE, FCC, RoHS   |
| Temperature     | – Operating Temperature: 0 ~ 50° C<br>– Storage Temperature: -10 ~ 70° C  |
| Dimensions      | – 330 (W) x 192 (D) x 44 (H) mm   |
| Packing         | – Net Weight: 3.5KG<br>– Gross Weight: 4.5KG<br>– Color Box dimension: 406 (W) * 359 (D) * 148 (H) mm   |
| OS Support      | – Windows 10 64bit, latest Linux kernel   |

Warranty

- 2 Year limited warranty