999.00 EUR
incl. 19% VAT, plus shipping

- Intel® Apollo Lake SoC Processor
- 1* DDR3L 1866MHz SODIMM up to 8 GB
- 4* USB3.1, 2* HDMI, 2* RJ45, 1* MIC/Line-out Combo, 1* COM (RJ45 type)
- Operating Temperature: -40 ~ 70° C
- M/B Form Factor : uTX (117x112mm)
- DC-12V_60W Adapter

| | |
|---|---|
| MB Model | – MT95-90 |
| Part No. | – HBFCT95-90B<br>– HBFCT95W-90B (WIFI) |
| BIOS | – AMI Flash ROM |
| CPU/Chipset | – Intel® Apollo Lake SoC Processor (E3940 CPU TDP 9.5W) |
| Memory | – 1* DDR3L 1866MHz SO-DIMM up to 8 GB |
| Network | – 2* Intel® i210AT GbE |
| Storage | – 1* M.2 M-key (2242) Support SATA interface |
| Expansion | – 1* M.2 E-key (2230) Support USB2.0 & PCIex1 interface (for WiFi module installed)<br>– 1* M.2 B-key (3042) Support USB3.0 interface (for 3G/4G/5G module installed) |

| | |
|---|---|
| Rear Panel I/O | – 2* USB3.1 (Gen1)<br>– 2* HDMI (Max. Resolution: 3840 x 2160@30Hz)<br>– 2* RJ45<br>– 1* MIC/Line-out Combo (Realtek® ALC662VD)<br>– 1* COM (RJ45 type)<br>– 2* Antenna holes (WiFi only)<br>– 1* DC-in jack (Lockable type) |
| Front Panel I/O | – 1* Power button<br>– 1* Power LED, 1* HDD LED, 2* LAN LED<br>– 2* USB3.1 (Gen1)<br>– 1* AT / ATX mode Switch |
| Power Source | – AC to DC Adapter / AC 90~240V_DC12V_5A_60W<br>– MT95-90 MB_DC 12V input |
| Compliance | – CE, FCC, LVD, RoHS, ErP Ready |
| Temperature | – Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD)<br>(The test environment is closed and windless)<br>– Storage Temperature: -40 ~ 80° C<br>– Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| Dimensions | – 144 (W) x 116.9 (D) x 65 (H) mm |
| OS Support | – Windows 10, Linux |