



198.00 EUR  
incl. 19% VAT, plus [shipping](#)

- 1x Mini-PCI
- Dual LAN !
- Compact Flash !



<b>Model</b>	• VIA EPIA SN18000G
<b>Processor</b>	• VIA C7 1.8GHz
<b>Chipset</b>	• VIA CN896 North Bridge • VIA VT8251 South Bridge
<b>System Memory</b>	• 2 DDR2 400/533/667 DIMM sockets • Up to 4GB Memory Support
<b>VGA</b>	• Integrated VIA Chrome9™HC Graphics Video acceleration
<b>Expansion Slots</b>	• 1 16-Lane PCI-E slot • 1 32-Bit miniPCI slot
<b>Onboard IDE</b>	• 1 UltraDMA 133/100/66 connector
<b>Onboard LAN</b>	• 1 VIA VT6103L 10/100Mbps Ethernet PHY • 1 VIA VT6130 PCI-E Gigabit Ethernet Controller
<b>Onboard Audio</b>	• VIA VT1708A High Definition Audio Codec
<b>Onboard TPM</b>	• Infineon SLB9635TT 1.2 (Trusted Platform Module)

<b>Onboard I/O Connectors</b>	<ul style="list-style-type: none"> <li>• 4 SATA II connectors</li> <li>• 2 Fan pin connectors: CPU/Sys FAN</li> <li>• 1 USB pin connectors for 2 additional USB 2.0 ports</li> <li>• 1 LVDS/TTL/DVI module connectors(an add-on card is required)</li> <li>• 1 CF(compact Flash) type I connector(share with IDE1)</li> <li>• 1 serial port pin connector for COM2 ( 5V/12V selectable)</li> <li>• 1 LPC header</li> <li>• 1 CIR pin connector(switchable for KB/MS)</li> <li>• 1 SIR pin connector (IRDA 1.0)</li> <li>• 1 SMBUS connector</li> <li>• 1 Digital I/O pin connector</li> <li>• 1 S/PDIF out pin connector</li> <li>• 1 Front-panel pin connector</li> <li>• 1 Front-panel audio pin connectors(MIC and Line-out)</li> <li>• ATX power connector</li> </ul>
<b>Back Panel I/O</b>	<ul style="list-style-type: none"> <li>• 1 PS2 mouse port</li> <li>• 1 PS2 keyboard port</li> <li>• 1 Serial port</li> <li>• 1 VGA port</li> <li>• 2 RJ-45 LAN connector</li> <li>• 4 USB 2.0 ports</li> <li>• 3 Audio jacks for MIC-In, Line-In &amp; Line-Out (5.1 Support)</li> </ul>
<b>BIOS</b>	<ul style="list-style-type: none"> <li>• AMI BIOS</li> <li>• LPC 4/8Mbit flash memory</li> </ul>
<b>Operating System</b>	<ul style="list-style-type: none"> <li>• Windows 2000/XP, Linux, Win CE, XPe</li> </ul>
<b>Management</b>	<ul style="list-style-type: none"> <li>• Fan control</li> <li>• CPU voltage monitoring</li> <li>• AC power failure recovery</li> <li>• System power management</li> <li>• Wake-on-LAN, Keyboard-power-on, Timer-Power-on,</li> <li>• Watch-Dog Timer,</li> </ul>
<b>Operating Temperature</b>	0°C ~ 50°C
<b>Operating Humidity</b>	0% ~ 95% (relative humidity; non-condensing)
<b>Form Factor</b>	<ul style="list-style-type: none"> <li>• Mini-ITX( 6 layers)</li> <li>• 17cm x 17cm</li> </ul>