



999.00 EUR  
 incl. 19% VAT, plus [shipping](#)



The HBFHP792X series is a ruggedized fanless automation PC. The DIN-rail mounting form factor is suitable to be used in control cabinet for industrial automation application. There are four models that can choose according to IO requirements.

MB Model	- JNP792V-2807
----------	----------------

	HBFHP792L-2807-G	HBFHP792G-2807-G	HBFHP792C-2807-G	HBFHP792U-2807-G
Part No	<ul style="list-style-type: none"> <li>- HBFHP792L-2807-G</li> <li>- HBFHP792LW-2807-G (WIFI)</li> </ul>	<ul style="list-style-type: none"> <li>- HBFHP792G-2807-G)</li> <li>- HBFHP792GW-2807-G (WIFI)</li> </ul>	<ul style="list-style-type: none"> <li>- HBFHP792C-2807-G</li> <li>- HBFHP792CW-2807-G (WIFI)</li> </ul>	<ul style="list-style-type: none"> <li>- HBFHP792U-2807-G</li> <li>- HBFHP792UW-2807-G (WIFI)</li> </ul>
CPU/Chipset	- Intel® Bay Trail N2807 Processor			
Memory	- 2GB DDR3L-1333 on board memory			
Storage	- 1 * full-size Mini-PCIe slot (for MSATA)			
Network	- 2 * Intel® GbE (MB / Intel i210IT)			
Expansion slot	<ul style="list-style-type: none"> <li>- 1 * M.2-2230 slot (for WiFi expansion)</li> <li>WiFi card – Support IEEE 802.11a/b/g/n/ac Wireless LAN 2T2R and Bluetooth 4.2</li> <li>– Support 802.11ac 2x2, Wave-2 compliant with MU-MIMO</li> </ul>			
Standard I/O	<ul style="list-style-type: none"> <li>- 1 * Power button , 1 * Power LED , 1 * HDD LED</li> <li>- 1 * USB 3.0 , 1 * USB 2.0</li> <li>- 1 * VGA , 2 * RJ45 (support WOL)</li> <li>- 1 * DC-In jack (Lock type)</li> </ul>			
Expansion I/O	<ul style="list-style-type: none"> <li>- 4 * RJ45 , 1 * RS232(RJ45 TYPE)</li> </ul>	<ul style="list-style-type: none"> <li>- GPIO (input – 16 PIN / output – 16 PIN)</li> </ul>	<ul style="list-style-type: none"> <li>- COM 1 ~ 2 / RS232(RS422 / RS485) , COM 3 / RS232</li> </ul>	<ul style="list-style-type: none"> <li>- 2 * USB 3.0 , 4 * USB 2.0 , 1 * RS232 (RS422 / RS485)</li> </ul>
Power Source	- FSP AC 90~240V to DC Adapter / DC12V-3.3A-40W / LV6			
Compliance	- CE, FCC, LVD, RoHS			
Temperature	<ul style="list-style-type: none"> <li>- Recommended Operating Temperature: 0 ~ 50° C</li> <li>- Working environment temperature: -20 ~ 70° C</li> <li>- Storage Temperature: -20 ~ 70° C</li> </ul>			
Dimensions	- 63 (W) x 89 (D) x 149 (H) mm			
Packing	<ul style="list-style-type: none"> <li>- Net Weight: 1.5KG</li> <li>- Gross Weight: 2.2KG</li> <li>- Color Box dimension: 152 (W) * 162 (D) * 260 (H) mm</li> </ul>			
OS Support	- Windows 7, Windows 8.1, Windows 10, Linux			
Warranty	- 2 Year limited warranty			