

98.00 EUR

incl. 19% VAT, plus [shipping](#)

- Motorized Pan/Tilt !
- Motorized Zoom !
- POE !
- Web Interface !



**Support:** [Manual \[EN\]](#) | [Software \(Windows\)](#) | [GUI Screenshots](#)

CTFCAM-1 is an IP-camera with PTZ-support (control camera head left/right, up/down via software) and motorized zoom (control zoom 2.8-12mm via software). The camera is powered via POE-LAN-connector. The camera has a web interface for playback/recording/configuration. She also can be connected to ONVIF compatible video recorders and/or be controlled by ONVIF compatible software.

#### Specifications :

Image Sensor 1080P: IMX323 + 1/3" Hi3518E

Max. Pixels 1920\*1080P

S/N Ratio 50dB(AGC Off)

BNC(HD-TVI/HD-CVI/AHD/CVBS)

LEDs & IR View 4\*High Power LED make max 80m IR distance , built in IR-CUT

Lens 4x Optical zoom, (f=2.8-12mm) motorized zoom, Auto Focus

White Balance Auto, ATW, Indoor, Outdoor, Outdoor Auto, Sodium Vapor Lamp Fix/Auto, One-push, Manual

Min. Illumination 0.01Lux @(F1.6,AGC ON) ,0 Lux with IR

Day & Night Auto(ICR) / Color / B/W

Video Compression H.264/MJPEG

S/N Ratio > 50 dB

Bit Rate 32K~16Mbps

Electronic Shutter 1/25-1/100000s

PTZ Mode 4 auto scan, 4 tour, 4 pattern

Network Functions TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/PPPOE/DDNS/NFS/ RTSP

Max Remote Users 128

Operating System Embedded Linux

Pan / Tilt Range Pan: 0°~270, Tilt: 0°~90°, Speed: 30°/sec

Preset 256 Preset (Camera Image Setting )

Protocol PELCO-P, PELCO-D

Working Humidity 0~95%(No condensation)

Working Temperature Outdoor: -35°C~+60°C

Power Supply : POE or 12V/2A

Size: 200mm x 171mm x 83mm

Weight: 1.5KG

Resource Simultaneous remote monitoring, remote operation & local recording