

459.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel® Skylake Celeron SoC Processor
- 1\* 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 16 GB
- 4\* 10/100/1000 Base-TX Ethernet Ports
- 1\* Full size Mini-SATA Socket (SATA + USB Signal)
- 2\* Mini PCIe Slots (1\* full size & 1\* half size)
- 1\* SIM card holder
- Supports on board TPM1.2/2.0 (option)
- 1\* RS232 Console, 2\* USB3.0, 2\* USB2.0
- Supports Antenna up to 4

MB Model	- JNF731-XXXX / 3.5" SBC
Part No	- HBFDF731-3855-B (non-WIFI) / HBFDF731W-3855-B (WIFI) - HBFDF731-3955-B (non-WIFI) / HBFDF731W-3955-B (WIFI) - HBFDF731-3965-B (non-WIFI) / HBFDF731W-3965-B (WIFI)
Processor	- Intel® Skylake Celeron 3855U/3955U/3965U SoC Processor
Chipset	- SoC Integrated
Memory	- 1 * SO-DIMM DDR4-2133MHz up to 16GB

Storage	<ul style="list-style-type: none"> <li>- 1 * 2.5" SATA3 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm)</li> <li>- 1 * full size mSATA</li> </ul>
Network	<ul style="list-style-type: none"> <li>- 1 * Intel® i219LM GbE &amp; 3 * Intel® i211AT (Default on board)</li> </ul>
Expansion slot	<ul style="list-style-type: none"> <li>- 1 * half size Mini PCIe slot (for WiFi expansion)</li> <li>- 1 * full size Mini PCIe slot with 1 * SIM card holder)</li> </ul>
Front Panel I/O	<ul style="list-style-type: none"> <li>- 1 * Power button, 1 * Reset button</li> <li>- 1 * Power LED, 1 * HDD LED</li> <li>- 2 * USB2.0</li> <li>- 4 * NIC LED</li> <li>- 1 * COM &amp; 1 * GPIO (option)</li> </ul>
Rear Panel I/O	<ul style="list-style-type: none"> <li>- 4 * RJ45 (3 * i211AT + 1 * i219LM)</li> <li>- 2 * USB3.0</li> <li>- 1 * HDMI (Reserve, Max. resolution:4096 x 2304@24Hz)</li> <li>- 1 * RS232</li> <li>- 1 * DC-in jack</li> </ul>
Other Features	<ul style="list-style-type: none"> <li>- TPM1.2 or TPM2.0 (On board option)</li> <li>- 0~255 segments by software programmable</li> </ul>
Power Source	<ul style="list-style-type: none"> <li>- FSP DC Adapter / AC 90~240V input / DC12V-5A-60W / LV6</li> </ul>
Safety	<ul style="list-style-type: none"> <li>- CE, FCC, LVD, RoHS</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating Temperature: 0 ~ 50° C</li> <li>- Storage Temperature: -10 ~ 70° C</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>- 193 (W) x 142.4 (D) x 62 (H) mm</li> </ul>
Packing	<ul style="list-style-type: none"> <li>- Net Weight: 2.2KG</li> <li>- Gross Weight: 3.2KG</li> <li>- Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm</li> </ul>
OS Support	<ul style="list-style-type: none"> <li>- 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux</li> </ul>
Warranty	<ul style="list-style-type: none"> <li>- 2 Year limited warranty</li> </ul>