



## 999.00 EUR incl. 19% VAT, plus <u>shipping</u>

- Intel Braswell !
- Mini-PCI Express !
- 2cm height !
- 10-19VDC Input !

This board is produced by MITAC, the OEM producer of Intel DN2800MT. This board is based on Intel DN2800MT, but is equipped with the moderm Intel Braswell plattform. PD10RI is available until at least 2025.

- Intel Braswell N3060 dual cores processor
- Intel HD graphics and DriectX 11 support
- Dual channel DDR3L with two connectors for MAX. 8GB memory
- Triple independent display from HD-Out, VGA, and Embedded Display-Port\* / LVDS connectivity
- Features high speed Gigabit Ethernet connection
- Features 2 SATA 3Gb/s
- Four Hi-Speed USB3.0 ports support
- Two Power RS232
- One PCIe connector for the future Add-in card
- Two PCI Express Mini Card connector for expansion card
- 8 V to 24 V wide-range voltage input via back-panel DC jack or internal power connector

Form Factor	Low-profile Mini-ITX (20 millimeters [0.79 inches] x 170.18 millimeters [6.7 inches] x 170.18 millimeters [6.7 inches])		
Processor Chipset	Intel Braswell N3060 Processor with integrated graphics		
Memory	<ul> <li>Support for dual channel DDR3L 1066/1333 SO-DIMMs</li> </ul>		
	<ul> <li>Support for up to 8 GB of system memory on a single SO-DIM</li> </ul>	Μ	
	(or 4 GB each by 2 SO-DIMM)		
	204-pin DDR3L SO-DIMM 2		
Graphics	Integrated graphics:		
	Digital displays (HD-Out)		
	Analog displays (VGA)		
	<ul> <li>Internal flat panel displays:</li> </ul>		
	• LVDS		
	<ul> <li>Embedded DisplayPort* eDP*</li> </ul>		
	<ul> <li>External graphics support via a PCI Express 1.0a x1 graphics add-in card connector</li> </ul>		
Audio	<ul> <li>2 + 2 Channel High Definition Audio (HD Audio) using a</li> </ul>		
	Realtek* ALC888S audio codec supporting:		
	Analog stereo line-out (back panel jack)		
	- In-chassis stereo speakers support (3 W/3 $\Omega$ via an internal header)		



Mitac PD10RI-N3060 (Intel DN2800MT3C) Half-Height (Intel Braswell N3060 2x2.48Ghz CPU, 10-19VDC) [FANLESS]

[http://www.minipc.de/catalog/il/2970]

PCI Express x1 add-in card connector	1	
PCI Express Full-/Half-Mini Card slot	1	
PCI Express Half-Mini Card slot	1	
USB 2.0 front panel ports	5 (Headers)	
USB 3.0 back panel connectors (blue)	4	
<ul> <li>SATA 3.0 Gb/s</li> <li>SATA 3.0 Gb/s port</li> </ul>	2	
	1	
•		
•		
,	6683D) that provides:	
	2	
Parallel port via an onboard		
header	1	
	Realtek RTL8111G-CG Gigabit (10/100/1000 Mb/s) Ethernet LAN	
LAN Support	controller including an RJ-45 back panel connector with integrated status LEDs	
<ul> <li>BIOS resident in a Serial Pe</li> </ul>	ripheral Interface (SPI) Flash device	
Support for Advanced Configuration and Power Interface		
(ACPI), and System Management BIOS (SMBIOS)		
Nuvoton NCT6104D based subsystem, including:		
<ul> <li>Voltage sense to detect out of range power supply voltages</li> </ul>		
Thermal sense to detect out of range thermal values		
3-pin system fan header		
<ul> <li>DC connectivity via back-participation</li> </ul>	nel DC jack(2.5mm/ ID, 5.5mm/ OD)	
<ul> <li>Internal 2 pin power connect</li> </ul>		
Operating Temperature: 0°C		
	C to +70°C	
• CE • FCC		
	<ul> <li>connector</li> <li>PCI Express Full-/Half-Mini Card slot</li> <li>PCI Express Half-Mini Card slot</li> <li>USB 2.0 front panel ports</li> <li>USB 3.0 back panel connectors (blue)</li> <li>SATA 3.0 Gb/s</li> <li>SATA 3.0 Gb/s port (multiplexed with an mSATA port, routed to the PCI Express Full-/Half-Mini Card slot)</li> <li>Legacy I/O Controller (NCT6 Powered RS232</li> <li>Parallel port via an onboard header</li> <li>LAN Support</li> <li>BIOS resident in a Serial Pe Support for Advanced Confi (ACPI), and System Manage Nuvoton NCT6104D based sub</li> <li>Voltage sense to detect out</li> <li>Thermal sense to detect out</li> <li>3-pin system fan header</li> <li>DC connectivity via back-pa</li> <li>Internal 2 pin power connect</li> <li>Operating Temperature: -20°C</li> <li>CE</li> </ul>	