



369.00 EUR
 incl. 19% VAT, plus [shipping](#)

- Whiskey Lake-U !
- 3,5" !
- 2x LAN !

- Intel® 8th Gen Whiskey Lake-U 1.6GHz/QC Core MCP Processor
- 2* DDR4 2400MHz, up to 64GB
- 1* Intel® I219LM GbE, 1* Intel® i225-V 2.5GbE
- 1* SATA III (6Gb/s), 1* M.2 (M-key), 1* M.2 E-key Support CNVi, 1* M.2 B-key Support 4G/5G Module
- 1* HDMI/DP + 1* eDP
- 2* RS232/422/485, 2* USB3.0, 3* USB2.0
- 12~36V DC in
- 3.5" Form Factor (146 * 102 mm)
- JLF0DV-42 support TPM2.0 (option)

Model	– JLF0DV-20 (8365UE) – JLF0DV-22 (8365UE, TPM2.0) – JLF0DV-40 (i5-8265U) – JLF0DV-42 (i5-8265U, TPM2.0) – JLF0DV-70 (4305UE) – JLF0DV-72 (4305UE, TPM2.0)
Form Factor	– 3.5" (146 * 102mm)
Processor System	– Intel® 8th Gen Whiskey Lake-U Quad Core MCP Processor – Intel SoC chipset – AMI 128Mb Flash ROM BIOS
Memory	– 2* DDR4 2400MHz DRAM SO-DIMM up to 64GB
Storage	– 1* M.2 M-key (2242/2280, SATA or NVMe- PCI-Ex4) – 1* SATAIII (6.0Gb/s)
Expansion Slot	– 1* M.2 E-key (2230, Support CNVi) – 1* M.2 B-key (3042/3052, Support 4G/5G Module) – 1* SIM Card Holder (Nano)

Ethernet	<ul style="list-style-type: none"> - 1* Intel® i219LM GbE - 1* Intel® i225-V 2.5GbE
Graphics	<ul style="list-style-type: none"> - Intel® HD Graphics, shared memory - 1* HDMI 1.4 (Max Resolution : 4096x2304@24Hz) - 1* DP (Max Resolution : 4096x2304@60Hz) - 1* eDP (Max Resolution : 4096x2304@60Hz) - Support Triple Displays
Audio	<ul style="list-style-type: none"> - USB Audio - 3W Amplifier speaker
Internal I/O	<ul style="list-style-type: none"> - 1* USB2.0 - 2* RS232/422/485 - 1* SATAIII - 3* M.2 (M-key, E-key, B-key) - 1* GPIO (8 bit, 5V) - 1* AT mode - 1* I2C/SMBUS - 1* FP_Audio - 1* Speaker - JLF0DV-42 support TPM2.0 (Option)
External I/O	<ul style="list-style-type: none"> - 1* HDMI - 1* DP - 2* RJ45 - 2* USB3.0 - 2* USB2.0 - Power button - Power LED, HDD LED - 12~36V DC-in jack
Watchdog Timer	<ul style="list-style-type: none"> - From Super I/O to drag RESETCON# - 256 segments (10sec ~ 255min)
Power	<ul style="list-style-type: none"> DC-in 12~36V, AT/ATX Supported - AT: Directly PWR on as Power input ready - ATX: Press Button to PWR on after Power input ready
Compliance	<ul style="list-style-type: none"> - CE, FCC, RoHS, REACH
Temperature	<ul style="list-style-type: none"> - Operating: 0°C ~ 60°C - Storage: -20°C ~ 70°C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 10, Linux