



1329.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake !
- i5-1135G7 !
- 15" Panel Computer !

- 15.0"350 nits TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Support Open frameless design
- A true Flat, easy-to-clean front surface with edge-to-edge design
- Front IP65 for protection against water and dust
- Aluminum Die-Cast Panel PC series, support for easy HDD and DARM installation
- Support Cable less design
- 12-36V DC-input Support, with Electrical Over Stress(EOS), OVP design
- VESA Support 100\*100mm

|                   |  |
|-------------------|--|
| Display           | <ul style="list-style-type: none"> <li>- IP65, NEMA 4 rugged protection, metal front bezel</li> <li>- 15.0" With LED Backlight</li> <li>- 350 nits</li> <li>- 16.7m display color</li> <li>- 1024 x 768 @60Hz resolution</li> <li>- 178°/178° viewing angle (H/V)</li> <li>- 0.099 x 0.297mm pixel pitch</li> <li>- 4:3 aspect ratio</li> <li>- 1000:1 contrast ratio</li> <li>- 35ms response time</li> </ul> |
| Touch Screen      | <ul style="list-style-type: none"> <li>- Projected capacitive type</li> <li>- 336.3 x 260.6mm ±0.3mm active range</li> <li>- Transparency ■85%</li> <li>- Surface Hardness ■6H (JIS-5400)</li> </ul>   |
| Case              | <ul style="list-style-type: none"> <li>- Aluminum panel</li> <li>- Iron case</li> <li>- White color</li> <li>- Spray paint coating requirement</li> </ul>  |
| Main System       | <ul style="list-style-type: none"> <li>- Intel® Tiger Lake i5-1135G7 2.4GHz/QC processor</li> <li>- 2* DDR4 SO-DIMM (Max 64GB)</li> <li>- 256MB SPI Flash ROM</li> <li>- Watchdog Timer 256 levels, 0~255 sec.</li> <li>- OS Support Windows 10 / Linux</li> </ul>   |
| Storage           | <ul style="list-style-type: none"> <li>- 1* 2.5" SATA HDD</li> <li>- 1* M.2 M key (2242/2280, PCI-Ex4)</li> </ul>  |
| Expansion         | <ul style="list-style-type: none"> <li>- 1* M.2 E key (2230) for WIFI</li> <li>- 1* M.2 B key (3042/3052/6570) for 4G/5G Module (4pcs Built in Antenna)</li> </ul>   |
| I/O Connector     | <ul style="list-style-type: none"> <li>- 2* USB3.2 (Gen. 1)</li> <li>- 4* USB2.0</li> <li>- 2* RS232/422/485</li> <li>- 2* RS232 (option 16bit GPIO)</li> <li>- 1* HDMI</li> <li>- 1* AT/ATX Mode Button</li> <li>- 2* RJ45 (1* Intel® I225-V 2.5GbE, 1* Intel® I219LM GbE)</li> <li>- 1* 12~36V DC-in Locking Jack</li> <li>- 1* Power button</li> <li>- 1* 2pin Front Power button</li> </ul>                |
| Power Input       | <ul style="list-style-type: none"> <li>- AC version: 100~240V AC-DC 90W power adapter or</li> <li>- DC version: 12VDC with over current protection fuse</li> </ul>   |
| Power Consumption | <ul style="list-style-type: none"> <li>- 45W</li> </ul>  |
| Dimensions        | <ul style="list-style-type: none"> <li>- 382.3 x 288.6 x 63.1mm</li> </ul>   |
| Compliance        | <ul style="list-style-type: none"> <li>- CE, FCC, IP65 (Front), Option</li> </ul>  |
| Safety            | <ul style="list-style-type: none"> <li>- Shock: 1ms duration</li> <li>- Vibration: 5~500Hz/1 Grms</li> </ul>   |
| Temperature       | <ul style="list-style-type: none"> <li>- Operating: : -10°C ~ 60°C</li> <li>- Storage: -20°C ~ 70°C</li> </ul>   |