



409.00 EUR

incl. 19% VAT, plus shipping

- Intel Atom N150, 6W !
- 2x 2.5GbE LAN !
- 6x COM, 6x USB !
- MTX-TWL1-N1500010 !

- Powered by onboard Intel® Atom® N150 Processor (Formerly Twin Lake, TDP 6W)
- Memory: 1 x DDR5 4800MT/s Single Channel SO-DIMM, up to 32GB
- Support up to three displays: 1 x Type-C DP, 2 x HDMI® 2.0b and 1 x LVDS/eDP
- Dual 2.5GbE LAN ports for fast and reliable networking
- Storage expansion with 1 x SATA III and 1 x M.2 M-Key for NVMe
- Additional expansion options: 1 x M.2 E-Key and 1 x M.2 B-Key for 4G/5G modules
- Comprehensive I/O: 1 x USB 3.2 Gen 2x1, 1 x USB 3.2 Gen 2x1 Type-C, 6 x USB 2.0 and 6 x COM ports
- Wide DC input range of 12-28V
- Intel® PTT (fTPM)

SYSTEM

MB FORM FACTOR

CPU

CHIPSET

MEMORY

BIOS

WAKE ON LAN

WATCHDOG TIMER

Mini-ITX

Onboard Intel® Atom® N150 Processor
(Formerly Twin Lake, TDP 6W)

Intel® SoC

1 x DDR5 4800MT/s, Single Channel SO-DIMM,
up to 32GB

UEFI

Yes

255 Levels

SECURITY	Intel® PTT (fTPM)
RTC BATTERY	Lithium Battery
DIMENSION (W X D)	170.0 (W) x 170.0 (D) mm (6.7" x 6.7")
OS SUPPORT	Windows® 11 (64bit) Windows® 10 (64bit) Linux
POWER	
POWER REQUIREMENT	DC-in 12~28V
POWER ON MODE	AT / ATX
CONNECTOR	DC Jack 4-pin Header
DISPLAY	
GPU	Intel® UHD Graphics
LVDS	1 x 24-bit Dual Channel LVDS (Max. Resolution: 1920 x 1080 @60Hz / Co-Lay eDP)
Type-C DP	1 x Type-C DP1.4 (Max Resolution: 4096 x 2160@60Hz)
HDMI®	2 x HDMI® 2.0b (Max Resolution: 4096 x 2160@60Hz)
MULTIPLE DISPLAY	Support 3 Displays
AUDIO	
CODEC	Realtek Audio Codec
COMBO	1 x Combo Audio Jack for Line-Out / Mic-In
AMPLIFIER	3W
LAN	
ETHERNET	2 x RJ45 for Intel® I226-V 2.5GbE
USB PORT	
USB	1 x USB 3.2 Gen 2x1 (10Gbps, Formerly USB 3.1 Gen 2) 1 x USB 3.2 Gen 2x1 Type-C (10Gbps) Support DP ALT Mode 2 x USB 2.0 Internal Header for 4 x USB 2.0
SERIAL PORT	
COM	1 x DB-9 for RS-232/422/485 with 5V/12V header Internal Header for 5 x RS-232 with 5V/12V header
INTERNAL I/O	
GPIO	8-Bit
SMBUS	Yes
FAN	1 x CPU Fan Header 1 x System Fan Header
FRONT PANEL	HDD Active LED, Power On/Off, Power LED, Reset
ADDITIONAL STORAGE	1 x PS/2

SATA	1 x SATA III 1 x SATA Power Connector
EXPANSION	
M.2	1 x M-Key 2242/2280 (SATA/PCIe 3.0 x2) Support NVMe 1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1) Support CNVi 1 x B-Key 3042/3052 (USB 3.2/USB 2.0) for 4G/5G Module 1 x Nano SIM Card Slot
SIM	
ENVIRONMENT & CERTIFICATION	
SHOCK	15G, 11ms duration
VIBRATION	1 Grms/ 5~ 500Hz/ Operation
OPERATING TEMPERATURE	-20°C ~ 60°C (-4°F ~ 140°F)
STORAGE TEMPERATURE	-20°C ~ 85°C (-4°F ~ 185°F)
OPERATING HUMIDITY	10 ~ 90% Relative Humidity, Non-condensing
CERTIFICATION	CE/FCC Class A
Packing List	MTX-TWL1 MB I/O Shield Heatsink COM Port Cable x 2 SATA Cable SATA Power Y Cable